

Introducing a New Economical Portable Water Source Solution



WT5C High Pressure Hose Water Tank Trailer

KEY FEATURES


- Capacity 525 gallons
- Rear, side and fire hose spray features
- Single lever controls for suction and discharge
- Multiple ports for flexible delivery options
- 200psi rated hose and nozzle options
- Baffled inner tank for safety and ease of over road towing
- Quick fill system minimizes down time

BUILT TO LAST

Professional quality and built for maximum utility and durability, the Superior water trailer is ideal for site dust control, equipment wash down, emergency use and more. The WT5C can be configured to your needs and it's flexibility for fill and discharge makes it the perfect choice for construction projects large and small.

SUPERIOR
STORAGE TANKS & TRAILERS

PH: 1-800-994-TANK (8265)
superior-tanks.com



SPECIFICATIONS

Engine	
Model	Honda GX120
Power - New Prime HP	3.5
Fuel Tank Gal.	0.66
Fuel Consumption GPH	0.18
Operating Speed RPM	3,600
Pump	
Make	Multiquip
Model	QP2H
Type	2" Centrifugal
Max Flow GPM	158
Max Head Ft.	115
Water Tank	
Type	Industrial Grade — Repairable
Style	Rotomolded with 6 baffles
Fill Port	12" vented port
Material	Polypropylene — 3/16" wall
Fill Rate	Five minutes full fill @ full throttle
Capacity Gal.	525
Water Operations	
Delivery Methods	Pressurized 1.5" and 2" left/ 2" right; Pressurized rear spray nozzles; Three standard garden hose adapters
Fill Methods	Municipal fire hydrant — QD; 1.5" and 2" Q/ D cam and groove; Two standard garden hose adapters
Trailer and Frame	
Material	Formed steel channel frame
Number of Axles	2
Capacity — Axle Rating lb.	3,500
Tires	ST205/75D 14"
Certification	DOT
Brakes	Surge brakes
Hitch	2-5/16" Ball / 3" Pintle
Jack Ratings lb.	2,000
Hose Bin	Formed steel enclosure
Hose Kit	2" x 20 ft. Suction (HSQ220) 2" x 50 ft. Discharge (HDQ250)
Size and Weight	
Dimensions LxWxH in.	146 x 68 x 80
Trailer Weight DRY lb.	1,530
Trailer Weight WET lb.	5,920